

9 LOW HEADROOM HOIST ND, REEVING: 02

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P5/T5 motor		F gear + P5/T5 motor		H gear + P6/T6 motor		J gear + P7/T7 motor	
		High	Low	High	Low	High	Low	High	Low
4000	3m/M6	8	1,3	10	1,7	16	2,7	20	3,3
5000	2m/M5	8	1,3	10	1,7	16	2,7	20	3,3
6300	1Am/M4	8	1,3	-	-	-	-	-	-

Hoist dimensions

HOL m	Length code	M1 mm	H2 mm	H3 mm	L12 mm	W mm	Weight kg
18	D	697	176	647	1058	708	595
24	E	817	235	767	1178	828	640
32	F	967	309	917	1328	978	690

Motor dimensions

Motor	P5	P6	P7	T5	T6	T7
M2 (mm)	728	722	762	728	722	722
Weight (kg)	58	85	105	45	65	71

Trolley dimensions

B min.	B max.	D1 (Ø)	D2 (Ø)	H1							
100	610	125	63	236							
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	
175	411	620	654	3	41	35	262	60	513	106	

D002112_A
059568

C-dimensions

B	C
100 - 199	630
200 - 259	600
260 - 440	580
441 - 540	640
551 - 610	680

Note: Weight calculated with P5 motor.

Note: All dimensions in mm.

