

27 DOUBLE GIRDER HOIST NE, REEVING: 04

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear		F gear		G gear		H gear		J gear	
		High	Low	High	Low	High	Low	High	Low	High	Low
		4	0,7	5	0,8	6,3	1,1	8	-	10	-
12500	3m/M6	P6/T6 motor		P6/T6 motor		P7/T7 motor		T8 motor		T9 motor	
16000	2m/M5	P6/T6 motor		P6/T6 motor		P7/T7 motor		T8 motor		T9 motor	
20000	1Am/M4	P6/T6 motor		P7/T7 motor		P8/T8 motor		T9 motor		TA motor	

Hoist dimensions

HOL m	Length code	M1 mm	M3 mm	H1 mm	H2 mm	Min R mm	Max R mm	Weight kg
7,5	C	462	658	668	69	1400	2400	1690
10,5	D	562	783	788	94	1700	2400	1790
14	E	682	783	788	125	1700	3100	1850
18	F	832	933	931	161	2000	3800	1950
23,5	G	1022	1143	1143	210	2400	4200	2110
30,5	H	1272	1479	1460	273	3100	4200	2300
40	J	1622	1543	1524	360	3400	4200	2610
48,5	K	1922	1969	1959	434	4200	4200	2960

Motor dimensions

Motor	P6	P7	P8	T6	T7	T8	T9	TA
M2 (mm)	536	576	711	536	536	536	536	576
Weight (kg)	85	105	106	65	71	81	92	106

Trolley dimensions

C	D1 (Ø)	D2 (Ø)	D3 (Ø)	WB	WW min	WW max					
922	140	170	63	1400	50	85					
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
428	472,6	400	122	100	51	1726	702	540	100	719	681
L13	L14	L15	L16	L17	L18	L19	L20	L21			
932	844	44	218	163	255	900	117	163			

D002144_A
005040

Note: Weight calculated with P6 motor.

Note: All dimensions in mm.

Note: Standard rail gauges: 1400, 1700, 2000, 2400, 2700, 3100, 3400, 3800 and 4200.

Note: H1, M3 and weight calculated with min R.

