

36 DOUBLE GIRDER HOIST NF, REEVING: 2 X 06

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear		F gear		G gear		H gear		J gear	
		High	Low	High	Low	High	Low	High	Low	High	Low
		2,5	0,4	3,2	0,5	4	0,6	5	-	6,3	-
40000	3m/M6	P6/T6 motor		P6/T6 motor		P7/T7 motor		T8 motor		T9 motor	
50000	2m/M5	P6/T6 motor		P6/T6 motor		P7/T7 motor		T8 motor		T9 motor	
60000	1Am/M4	P6/T6 motor		P7/T7 motor		T8 motor		T9 motor		-	

Hoist dimensions

HOL m	Length code	M1 mm	M3 mm	Min R mm	Max R mm	C mm	Weight kg
5	F	832	434	1700	2000	1516	2800
6,5	G	1022	364	2000	2400	1516	2900
9	H	1272	364	2000	2700	1516	3200
12,5	J	1622	389	2400	3100	1570	3450
15	K	1922	389	2700	3400	1570	3750
18,5	L	2272	414	3100	3800	1624	4050
20,5	M	2522	439	3400	4200	1624	4300
23,5	N	2822	489	3800	4200	1624	4550

Motor dimensions

Motor	P6	P7	T6	T7	T8	T9
M2 (mm)	536	576	536	536	536	536
Weight (kg)	85	105	65	71	81	92

Trolley dimensions

D1 (Ø)	D2 (Ø)	D3 (Ø)	WB	WW min	WW max						
280	250	100	1400	55	100						
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
488	600	80	135	526	20	1910	702	680	150	700,5	699,5
L13	L14	L15	L16	L17	L18	L19	L20	L21			
975,5	954,5	44	218	255	1013	255	155	315			

D002336_A
062408

Note: Weight calculated with P6 motor.

Note: All dimensions in mm.

Note: Min R with service platform.

Note: Standard rail gauges: 1700, 2000, 2400, 2700, 3100, 3400, 3800 and 4200.

Note: M3 and weight calculated with min R.

