

## 57 NORMAL HEADROOM HOIST ND, REEVING: 02, CURVED TRACK

### Hoist dimensions

HOL m	Length code	M1 mm	H2 mm	H3 mm	H3* mm	Weight kg
18	D	558	176	625	645	810
24	E	678	235	625	645	870
32	F	828	309	625	645	940
40	G	1018	403	625	645	1000

### Motor dimensions

Motor	P5	P6	P7	A5	S5	S7
MOT (mm)	578	578	618	498	606	757
Weight (kg)	58	85	105	45	53	81

### Travelling dimensions

Motor	MF06MA	MF06LA
TMO (mm)	360	400
Weight (kg)	5.7	7.8

### Trolley dimensions

B min	B max	C	ØBU	ØWD	BU	BUH	GEA	H1	H4	M2	TD
90	350	1230	63	100	253	40	143	389	667	154	850
TF	TH	TW									
42	150	31									

D004135\_A  
062273

### Trolley dimensions

Length code	TS	BUF
D/E	520	957
F/G	640	1297

### Track radius

B	R min
90 - 109	2500
110 - 119	2000
120 - 350	1500

Note: All dimensions in mm.

Note: Weight calculated with P5 motor.

Note: Motor S7 is unavailable for load class 6300 kg.

\* Please, disregard the dimension H3\*.

Normal Headroom Hoist ND, REEVING: 02, Curved Track

