

## 74 NORMAL HEADROOM HOIST NC, REEVING: 04, CURVED TRACK

### Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P3/T3 motor		F gear + P3/T3 motor		H gear + P4/T4 motor	
		High	Low	High	Low	High	Low
4000	3m/M6	4	0,7	5	0,8	8	1,3
5000	2m/M5	4	0,7	5	0,8	8	1,3

### Hoist dimensions

HOL m	Length code	M1 mm	H2 mm	Weight kg
6	B	467	49	360
9	C	567	73	400
12	D	667	97	550
15	E	787	121	565

### Motor dimensions

Motor	P3	P4	T3	T4
M2 (mm)	597	690	507	610
Weight ( kg)	35	53	22	45

### Trolley dimensions

B1 min	B1 max	B2 min	B2 max	C1	C2	D1 (Ø)	D2 (Ø)	H1			
80	450	90	350	870	1030	63	100	292			
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
506	16	172	161	88	412	31	4	40	40	150	426
L13	L14	L15	L16	L17	L18	L19	L20	L21	L22	L23	L24
581	3	644	532	1029	253	523	95	62	44	2	42
L25	L26	L27	L28	L29	L30	L31	L32	L33	L34	L35	L36
742	4	800	706	511	47	228	250	42	125	140	34

D003841\_A  
062169

### Track radius

B	R min
80 - 109	2500
110 - 119	2000
120 - 450	1500

Note: Weight calculated with P3 motor.

Note: All dimensions in mm.

Note: L29 with one cubicle only, L28 with optional cubicle, L27 with two RST cubicles.

