

78 NORMAL HEADROOM HOIST NC, REEVING: 08, CURVED TRACK

Hoisting speed (m/min)

Load kg	Class Fem/ISO	F gear + P3/T3 motor		H gear + P4/T4 motor	
		High	Low	High	Low
8000	2m/M5	2,5	0,4	4	0,7
10000	1Am/M4	2,5	0,4	4	0,7

Hoist dimensions

HOL m	Length code	M1 mm	M3 mm	H2 mm	Weight kg
4,5	C	567	600	37	640
6	D	667	600	49	670
7,5	E	787	600	64	710

Motor dimensions

Motor	P3	P4	T3	T4
M2 (mm)	597	690	507	610
Weight (kg)	35	53	22	45

Trolley dimensions

B min	B max	C	D1 (Ø)	D2 (Ø)	H1						
80	350	1317	63	100	258						
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
1106	253	90	412	2	150	40	42	710	426	7	612
L13	L14	L15	L16	L17	L18	L19					
588	800	706	511	47	228	250					

D003843_A
062188

Track radius

B	R min
90 - 109	2500
110 - 119	2000
120 - 350	1500

Note: Weight calculated with P3 motor.

Note: All dimensions in mm.

Note: L16 with one cubicle only, L15 with optional cubicle, L14 with two RST cubicles.

