

80 NORMAL HEADROOM HOIST ND, REEVING: , CURVED TRACK02

Hoisting speed (m/min)

Load kg	Class Fem/ISO	E gear + P5/T5 motor		F gear + P5/T5 motor		H gear + P6/T6 motor		J gear + P7/T7 motor	
		High	Low	High	Low	High	Low	High	Low
4000	3m/M6	8	1,3	10	1,7	16	2,7	20	3,3
5000	2m/M5	8	1,3	10	1,7	16	2,7	20	3,3
6300	1Am/M4	8	1,3	-	-	-	-	-	-

Hoist dimensions

HOL m	Length code	M1 mm	M3 mm	H2 mm	Weight kg
18	D	697	520	176	810
24	E	817	520	235	870
32	F	967	640	309	940
40	G	1157	640	403	1000

Motor dimensions

Motor	P5	P6	P7	T5	T6	T7
M2 (mm)	728	722	762	728	722	722
Weight (kg)	58	85	105	45	65	71

Trolley dimensions

B min	B max	C	D1 (Ø)	D2 (Ø)	H1						
90	350	1230	63	100	389						
L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12
1026	253	18	88	1146	218	412	40	42	842	513	671
L13											
601											

D004135_A
062273

Track radius

B	R min
90 - 109	2500
110 - 119	2000
120 - 350	1500

Note: Weight calculated with P5 motor.

Note: All dimensions in mm.

